

United States Patent [19]

Scordato

[11] Patent Number: 4,881,259

[45] Date of Patent: Nov. 14, 1989

[54] ANSWERING MACHINE WITH CORDLESS TELEPHONE

[75] Inventor: James Scordato, Elmhurst, Ill.

[73] Assignee: Dynascan Corporation, Chicago, Ill.

[21] Appl. No.: 294,429

[22] Filed: Jan. 6, 1989

[51] Int. Cl.⁴ H04B 7/26

[52] U.S. Cl. 379/58; 379/67;
379/56; 379/61; 340/311.1

[58] Field of Search 379/56, 57, 58, 61,
379/62, 67, 88, 63; 340/825.44, 311.1

[56] References Cited

U.S. PATENT DOCUMENTS

4,475,009	10/1984	Rais et al.	379/211
4,481,382	11/1984	Villa Real	379/61
4,499,567	2/1985	Armstrong	369/7
4,500,752	2/1985	Lee	379/61
4,571,457	2/1986	Hattori et al.	379/56
4,625,081	11/1986	Lotito et al.	379/88
4,640,987	2/1987	Tsukada et al.	379/62
4,650,931	3/1987	Tsukada et al.	379/61
4,680,785	7/1987	Akiyama et al.	379/57
4,706,274	11/1987	Baker et al.	379/67
4,747,122	5/1988	Bhagat et al.	379/57
4,747,124	5/1988	Ladd	379/67
4,759,052	7/1988	Hashimoto	379/67
4,782,508	11/1988	Borchering et al.	379/67
4,794,637	12/1988	Hashimoto	379/67
4,797,909	1/1989	Mastromuro et al.	379/67

FOREIGN PATENT DOCUMENTS

0024245	2/1983	Japan	458/73
0138134	8/1983	Japan	379/58
0036438	2/1984	Japan	379/58
0100659	6/1984	Japan	379/61
0085632	5/1985	Japan	379/58
0241443	10/1987	Japan	379/58
2051520	1/1981	United Kingdom	379/58


Primary Examiner—Robert Lev



Attorney, Agent, or Firm—Wallenstein, Wagner & Hattis, Ltd.

[57] ABSTRACT

A cordless telephone and an answering machine of the remote-pickup type are provided as an integrated unit having the answering machine and telephone base unit integrated into a common housing. The remote handset contains circuitry for generating a command signal condition at the user's option which will operate the base unit to a "screening mode" wherein the activity on the telephone lines during the playback and record period is transmitted to the remote unit, but wherein audio pass-through from the base unit radio receiver is disabled. In the preferred form of the invention the command signal condition is in the form of a pilot tone of a given frequency, receipt of which by the base unit receiver disables audio pass-through. To enter two-way "talk" mode, a pilot tone of different frequency is also sent by the remote unit, loss of this tone being being to cause the base unit to cease transmitting to the remote unit.

11 Claims, 15 Drawing Sheets








FIG. 4.

